

Features:

- Long Life Battery operation
- Economical
- Small & Rigid design

Description:

The RFRxV016-608 is a Broadband Power Detector which operates from 1MHz to 6GHz with the capability to measure the RF signal in decibel-scaled output. The input dynamic range is typically 50 dB (referenced to 50 Ω) with less than ±3 dB error. They are used in various communication test setups for accurate measurements. RFRxV016-608 is a portable, cost effective as well as fulfils all quality standards. Stability over temperature is ±0.5 dB.

Applications:


- Scientific equipment manufacturer
- Power monitoring in radio link transmitters
- RSSI measurement in base stations, WLANs, WiMAX and radars.
- EMC Test laboratories
- Microwave system manufacturer
- Antenna manufacturer
- Bluetooth, Laura and Zigbee device manufacturer
- Testing of shielding effectiveness
- Engineering and technology colleges
- GSM and CDMA mobile towers



Electrical Specifications:

Frequency Range:	1 MHz to 6 GHz
Dynamic Range:	
1 – 6000 MHz	-5 to -55 dBm
Amplitude Variation:	
Broadband Mode	± 3 dB
Precise Mode	± 1.5 dB
VSWR:	2:1, all Phases
Output Impedance:	50 Ohm
Peak Power Units	dBm & dBuV
Display :	4 Digit 7 Segment LED
Operating Temperature:	0 °C to 50 °C
Battery Operation :	8 Hour for single charge
Connector:	SMA Female
Power Consumption:	0.3 Watt (Max.)

Mechanical Specifications:

Dimension(mm) :	(A) = 138.2 (H) = 115 (S) = 66.4	
Shape:	Hexagonal shape	
Weight:	300 gm	

Standard Accessories:

- SMA(M) to SMA(M) 50 Ohms cable 10" (Figure1)
- Charger (Figure 2)



Figure 1




Figure 2

